

Safety Data Sheet (CANADA)

1. Identification

Product Identifier: Propane, odorized

Other Means of Identification: Propyl Hydride, Dimethyl Methane, 1-Propene Tetramer, L.P.G. (Liquefied Petroleum Gas)

Product use: Fuel for heating, cooking, automobiles, welding/cutting; refrigerant, aerosol propellant

Restrictions on use: Do not use for purposes other than those listed above

Manufacturer: Keyera and Affiliates





Address: Suite 600, Sunlife Plaza West
144 – 4th Avenue SW
Calgary, AB, T2P 3N4

SDS Information: 1-780-449-7910

Emergency Contact (24 hours): 1-613-996-6666 (CANUTEC, Canada)
1-800-424-9300 (CHEMTREC, U.S.)

2. Hazards Identification

GHS Hazards

Pictogram	Classification	Hazard Statements
	Flammable Gases – Category 1	Extremely flammable gas
	Gases Under Pressure – Liquefied Gas	Contains gas under pressure; may explode if heated.
	Specific Target Organ Toxicity, Single Exposure – Category 2	May cause damage to heart.
	Specific Target Organ Toxicity, Single Exposure – Category 3	May cause drowsiness or dizziness.
No pictogram	Simple Asphyxiant	May displace oxygen and cause rapid suffocation.

Other Hazards

- May cause frostbite upon sudden release of liquefied gas.



Signal Word: Danger

Precautionary Statements:

Prevention

- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources – No smoking.
- Do not breathe gas.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/ protective clothing/ eye protection/ face protection when handling liquefied propane.

Response

- Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
- In case of leakage, eliminate all ignition sources.
- If inhaled: Remove person to fresh air and keep comfortable for breathing.
- If exposed or concerned: Call a doctor/physician.

Storage

- Protect from sunlight.
- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.

Disposal

- Dispose of contents/container in accordance with applicable local, provincial/state, and federal regulations.

3. Composition/Information on Ingredients

Chemical Name: Propane
Common Name/Synonyms: Propyl Hydride, Dimethyl Methane, 1-Propene Tetramer, L.P.G. (Liquefied Petroleum Gas)

Ingredient Name	Volume %	CAS No.
Methane	0 – 0.3	74-82-8
Ethane	0.5 – 5.0	74-84-0
Propane	94.0 – 99.9	74-98-6
iso-Butane	0 – 2.0	75-28-5
n-Butane	0 – 0.5	106-97-8
Ethyl Mercaptan (Ethanethiol)	20 – 25 ppm	75-08-1

4. First Aid Measures

Immediate Medical Attention and Special Treatment:

Treat symptomatically and supportively. Refer also to Table below.

First Aid:	
Inhalation:	Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Call a doctor/physician.
Skin:	If cold, liquefied propane is on skin (or hair): take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: get medical advice/attention.
Eyes:	Rinse cautiously with water for several minutes. If eye irritation persists: get medical advice/attention.
Ingestion:	Not expected to be a route of exposure.

Most Important Effects and Symptoms, Acute or Delayed:

Exposure Route	Health Effects	Symptoms of Exposure
Inhalation:	Propane may act as an asphyxiant by displacing oxygen in the ambient air, causing suffocation.	Loss of consciousness, death.
Skin:	Contact with liquefied gas may cause burn or frostbite.	numbness, cold, burning sensation, white, pale, greyish-yellow or red skin, blistering in severe cases.
Eyes:	Contact with liquefied gas may cause burn or eye damage.	numbness, cold or burning sensation, blistering to blindness in severe cases.

5. Fire Fighting Measures

<p>Flammability: Yes. Propane, liquefied or in gas form, are highly flammable.</p>	<p>Hazardous Combustion Products: Carbon monoxide (CO), carbon dioxide (CO₂), and acrid smoke.</p>
<p>Explosion: Sensitive to impact: No</p>	<p>Sensitive to static discharge: Yes</p>
<p>Extinguishing Media: Small Fire: dry chemical or CO₂. Large Fire: water spray or fog.</p>	
<p>Unsuitable Extinguishing Media:</p> <ul style="list-style-type: none"> • Foam. • Water jet: Do not direct water at source of leak, especially with LPG to avoid icing. 	
<p>Special Protective Equipment for Firefighters:</p> <ul style="list-style-type: none"> • Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face-piece. • Wear thermal protective clothing when the fire involves liquefied propane. 	
<p>Precautions for Firefighters:</p> <ul style="list-style-type: none"> • DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. • If tank, rail car or tank truck is involved in a fire, ISOLATE and consider initial evacuation <u>in all directions</u> for 1600 meters (1 mile). • Move container from fire area if you can do it without risk. • Apply cooling water to sides of containers exposed to flames until well after fire is out. • Cool fire-exposed containers with flooding quantities of water applied from as far a distance as possible. • Stay away from ends of tanks. • Containers exposed to fire may explode or vent through pressure-relief devices. • Refer to Guide 115 of the Emergency Response Guidebook (Transport Canada/US Dept. of Transportation). 	
<p>Unusual Fire and Explosion Hazards:</p> <ul style="list-style-type: none"> • The highly flammable vapors are heavier than air and may accumulate in low areas and /or spread along ground to distant ignition sources and flash back. 	

6. Accidental Release Measures

Protective Equipment:

Gloves: Recommended: neoprene and nitrile.
 Not recommended: polyvinyl chloride PVC.

Clothing: Flame-retardant coverall e.g. Nomex, Proban. Protective apron and trousers worn over coveralls for handling liquefied propane.

Respirator: NIOSH Approved Supplied-Air Respirator or SCBA where large propane concentration is anticipated, and the exposure level is unknown or where an oxygen-deficient atmosphere may exist.

Eye: Safety glasses with side shields, safety goggles or face shields.

Large spills: wear full protective clothing and NIOSH-approved SCBA with full face-piece.

Precautions:

- Direct addition of water to liquefied gas will cause flash vaporization resulting in an explosion (either immediately or delayed) called "boiling liquid, expanding vapor explosion (BLEVE)".
- Do not breathe gas/vapors.
- Do not touch spilled liquefied propane with bare skin to avoid frostbite/freeze burn.
- Liquefied propane is still highly flammable: must be kept from sparks, open flame, hot surfaces, and all sources of ignition and heat.
- The highly flammable vapors are heavier than air and may accumulate in low areas and /or spread along ground to distant ignition sources and flash back.

Emergency Procedures:

- Shut off leak/release source, if it can be done safely.
- Remove all sources of ignition.
- Isolate hazard area.
- Evacuate area of all unnecessary personnel.
 Small spill: will evaporate.
 Large spill: consider downwind evacuation of at least 800 meters (½ mile.)
 If tank, rail car or tank truck is involved in a fire, ISOLATE and consider initial evacuation in all directions for 1600 meters (1 mile).
- Keep unnecessary and unprotected personnel from entering.
- Emergency personnel must wear appropriate personal protective equipment.
- Ventilate area of leak or spill.
- If possible, turn leaking LPG containers so that gas escapes instead of liquid.

Containment and Clean-up:

- Use non-sparking tools and equipment.
- Contain and recover liquid if it can be done safely: Collect spillage with an inert material (e.g., vermiculite, dry sand, earth), and place in metal container which can be grounded.
- Do not use combustible materials, such as sawdust, as absorbent.
- If a leak or spill has not ignited, use water spray to disperse the vapors or divert vapor cloud draft. Do not direct water at spill or source of leak.
- Prevent vapors or LPG from spreading to sewers, ventilation systems, confined spaces.
- Dispose of contents/container in accordance with applicable local, provincial/state, and federal regulations.
- Refer to Guide 115 of the Emergency Response Guidebook (Transport Canada/US Dept. of Transportation).

7. Handling and Storage

Handling Precautions :

- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces – No smoking.
- Do not breathe gas/vapors.
- Do not eat, drink or smoke when using this product.
- Use non-sparking tools and equipment.
- Wear protective gloves/ protective clothing/ eye protection/ face protection when handling liquefied propane.
- Odor Fade: skunky-odored ethyl mercaptan was added to odorless propane as a warning agent. However ethyl mercaptan can chemically react and/or be absorbed by other materials (e.g. water/moisture, porous materials such as concrete, or rust inside tank or cylinder) resulting in the propane essentially deodorized.

Storage Precautions:

Locations

- Store in a cool, dry, well-ventilated location, away from any area of fire-hazard.
- Outside or detached storage is preferred.
- Storage and use areas should be No Smoking areas.
- Store locked-up.

Containers

- Keep container tightly closed.
- Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death

Other precautions

- Separate from incompatibles like oxidizers e.g. chlorine gas and oxygen.

8. Exposure Controls / Personal Protection

EXPOSURE LIMITS

	Authority	15 MINS STEL or Ceiling	8-HOURS
Methane* (CAS 74-82-8)	Alberta	-	-
	Ontario, BC	-	1000 ppm
Ethane* (CAS 74-84-0)	Alberta, Ontario, BC	-	1000 ppm
Propane* (CAS 74-98-6)	Alberta, Ontario, BC	-	1000 ppm
Butane (all isomers)	Alberta	-	1000 ppm (2370 mg/m ³)
	Ontario	-	800 ppm (1900 mg/m ³)
	BC	750 ppm (1778 mg/m ³)	600 ppm (1422 mg/m ³)
Ethyl Mercaptan (CAS 75-08-1)	Alberta	-	0.5 ppm (1.3 mg/m ³)
	Ontario, BC	-	0.5 ppm

* Identified as chemicals which may cause asphyxia according to ACGIH. According to the U.S. National Institute for Occupational Safety & Health, an oxygen deficient atmosphere is one with an ambient pO₂ less than 132 torr. at sea level the minimum requirement is 19.5% oxygen (148 torr pO₂). The partial pressure of oxygen decreases significantly with increase in altitude.

Because L.P.G. may cause asphyxia at concentrations well above the lower explosive limit (LEL), the revised IDLH for L.P.G. is 2,000 ppm based strictly on safety considerations (i.e., being about 10% of the LELs of 1.9% for butane and 2.1% for propane)



ENGINEERING CONTROLS

- Ventilate area where product is used, stored and/or handled to maintain airborne concentrations below the LEL and OEL, especially in confined spaces.
- Exhaust/ventilate to the outside.
- Ventilation equipment must be explosion proof.
- Ventilation system should be grounded and separate from other exhaust ventilation systems. Adequate make-up air must be provided.



PERSONAL PROTECTIVE EQUIPMENT

- Gloves: Recommended: neoprene and nitrile;
Not recommended: polyvinyl chloride PVC.
- Clothing: Flame-retardant coverall e.g. Nomex, Proban. Protective apron and trousers worn over coveralls for handling liquefied propane.
- Respirator: NIOSH Approved Supplied-Air Respirator or SCBA where large propane concentration is anticipated, and the exposure level is unknown or where an oxygen-deficient atmosphere may exist.
- Eye: Safety glasses with side shields, safety goggles or face shields.

9. Physical and Chemical Properties

Chemical Formula: C ₃ H ₈ or CH ₃ CH ₂ CH ₃		Molecular Weight: 44.10 g/mole	Chemical Family: Hydrocarbon
Appearance: Colorless gas		Odor: Skunk-like odor from addition of ethyl mercaptan	Odor Threshold: 0.76 ppb (ethyl mercaptan)
Odor Fade: skunky-odored ethyl mercaptan was added to odorless propane as a warning agent. However ethyl mercaptan can chemically react and/or be absorbed by other materials (e.g. water/moisture, porous materials such as concrete, or rust inside tank or cylinder) resulting in the propane essentially deodorized.			
pH: Not applicable	Melting/Freezing Point: -189.7°C (-309.5°F)	Boiling Point: -42.1°C (-43.8°F)	Boiling Range: Not available
Flash Point: -104°C (-156°F) Closed Cup		Flammability: Yes	Evaporation Rate: >1 (Butyl Acetate = 1)
Upper-Lower Explosive Limit: 2.1% (LEL), 10.0% (UEL)		Vapor Pressure: ~ 1303 kPa @ 37.8°C (100°F) (9774 mm Hg)	Vapor Density: 1.52 (air = 1)
Density: Gas: 1.91 kg/m ³ @ 15°C (59°F) Liquid: 500-580 kg/m ³ (36.2 lb/ft ³)		Soluble in water (@20°C): Slightly soluble: 0.024-0.061 g/L	Percent Volatile: 100 by volume
Partition Coefficient n-octanol/water: 2.3		Auto-Ignition Temperature: 470°C (878°F)	Decomposition Temp.: Not available
Viscosity: Not available		Henry's Law Constant: Not available	Isobaric Heat Capacity: Not available

10. Stability and Reactivity

Reactivity: Avoid incompatible materials: may react violently with oxidizers.
Chemical Stability: Stable under normal temperatures and pressures.
Possibility of Hazardous Reactions: Polymerization has not been reported to occur under normal temperature and pressure conditions.
Conditions to Avoid: Extreme temperatures and incompatible materials.
Incompatible Materials: <ul style="list-style-type: none"> • <u>Oxidizers</u>: may react violently with oxidizers including chlorine gas and oxygen.
Hazardous Decomposition Products: <ul style="list-style-type: none"> • No decomposition if stored and applied as directed. • Combustion forms carbon monoxide, carbon dioxide, irritating and toxic fumes/gases.

11. Toxicological Information

Exposure Route	Acute Health Effects	Symptoms of Exposure
Inhalation:	Effects on the Central Nervous system (CNS) may range from mild (respiratory depression) to severe effects (asphyxiation)	may range from rapid breathing, dizziness to respiratory arrest, loss of consciousness (narcosis) and death in extreme cases.
Skin:	In gas form: no known effects.	-
	In liquid form: burn or frostbite.	numbness, cold or burning sensation, white, pale, greyish-yellow or red skin, blistering in severe cases.
Eye:	In gas form: no known effects.	-
	In liquid form: burn or frostbite.	numbness, cold or burning sensation, blistering to blindness in severe cases.
Ingestion:	Not expected to be a route of exposure.	

Chronic Exposure:

Inhalation:
Repeated or prolonged exposure may cause damage to the central nervous system (CNS), the nervous and the heart system.

Skin:
Not known to be a skin-sensitizer. Repeated and prolonged contact may cause dry, red, cracked skin (dermatitis).

Medical Conditions Aggravated by Exposure:
Possibly asthma.

Sensitization: No	Reproductive Toxicology: No	Teratogenicity: No	Mutagenicity: No
Carcinogenicity: Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.	Irritancy: No.	Target Organs: Single exposure: central nervous system (CNS), heart. Repeated exposure: no data available.	

Lethality Tests:

Chemical Name	CAS No.	LC50	
Ethane	74-84-0	Rat, inhalation: 658 mg/L 4 hrs.	
Propane	74-98-6	Rat, inhalation: >800000ppm, 15-mins (oxygen was also added to maintain a level of ~20vol%)	
		Rat, inhalation: 658 mg/L 4hrs.	
n-Butane	106-97-8	Rat, inhalation: 658 mg/L 4hrs.	
Isobutane	72-28-5	Rat, inhalation: 658 mg/L 4hrs.	
Ethyl Mercaptan (Ethanethiol)	75-08-1	LC50	LD50
		Rat, inhalation: 2770 ppm/4hr. Mouse, inhalation: 4420 ppm/4hr	Rat, ip: 226 mg/kg Rat, oral: 682 mg/kg

12. Ecological Information

Persistence & Degradability: Not expected to persist in the environment.	Bioaccumulative Potential: No.
Mobility: No data available.	Other Adverse Effects: See below.

Terrestrial Fate:

- Photolysis and hydrolysis are not expected to be important in soil.
- Not expected to bioaccumulate.
- Propane is readily degraded by soil bacterium; within 24 hr. propane was oxidized to acetone.
- Volatilization from soil surfaces is expected to be an important fate process based upon an estimated Henry's Law constant of 7.07×10^{-1} atm-cu m/mole. Groundwater contamination is not expected.

Aquatic Fate:

- Propane is only slightly soluble in water. Spills will spread on the water surface and the majority will evaporate. Estimated volatilization half-lives for a model river and model lake are 41 min and 2.6 hours, respectively.
- Hydrolysis is not expected to be an important environmental fate process since this compound lacks functional groups that hydrolyze under environmental conditions.
- Propane is not listed as a marine pollutant by DOT (49 CFR Part 171).

Atmospheric Fate:

- If released to air, a vapor pressure of 7,150 mm Hg at 25°C indicates propane will exist solely as a gas in the atmosphere.
- Propane is not expected to be susceptible to direct photolysis by sunlight, but will be degraded in the atmosphere by reacting with hydroxyl radicals; the half-life for this reaction in air is estimated to be 14 days.
- Propane also has the potential to partake in photochemical reactions to produce ozone pollutant at ground level.
- Propane does not contain any Class I or II ozone-depleting chemicals (40 CFR Part 82).

Eco Toxicity Tests:

- Not available.

13. Disposal Considerations

Waste Disposal:

- Dispose of waste material at an approved waste treatment/disposal facility in accordance with applicable local, provincial, and federal regulations.
- Excess/waste propane can be disposed by incineration in a waste gas incinerator or flare.
- Propane can also be reused as fuel for boilers and heaters.

14. Transport Information

TDG (CANADA) CLASSIFICATION

PROPER SHIPPING NAME: Propane
CLASS: 2.1
PACKING GROUP: None

UN NUMBER: UN1978
LABEL/PLACARD:



SPECIAL PROVISION: 88

Despite the quantity limits in column 9 of Schedule 1 for these dangerous goods, a road vehicle is not a passenger carrying vehicle unless the passengers in it are transported for hire or reward.

OR

PROPER SHIPPING NAME: Liquefied Petroleum Gas (Propane)
CLASS: 2.1
PACKING GROUP: None
SPECIAL PROVISION: None

UN NUMBER: UN1075
LABEL/PLACARD:



MARINE POLLUTANT: No.

15. Regulatory Information

CANADA

	Methane	Ethane	Propane	n-Butane	iso-Butane
	CAS#	CAS#	CAS#	CAS#	CAS#
	74-82-8	74-84-0	74-98-6	106-97-8	75-28-5
DSL Domestic Substance List	yes	yes	yes	yes	yes
NPRI	no	no	Yes		
National Pollutant Release Inventory	(as VOC Volatile Organic Compound)				
E2	yes	yes	yes	yes	yes
Environmental Emergency substance	yes	no	no	no	no
Canada CEPA 2009 GHG & Alberta Specified Gas Reporting Reg.	yes	no	no	no	no

16. Other Information

NFPA Hazard Rating:
Health 1, Flammability 4, Instability 0



Prepared for: Keyera Health and Safety
Issue Date/ Revision No: August 31, 2015, 2015/ Revision #4

Revisions:	Dates:	Main Changes
• Original:	January 3, 2011	
• 1 st revision:	January 31, 2014	Reformat
• 2 nd revision:	June 30, 2015	Canada GHS/WHMIS-2015 format
• 3 rd revision:	July 30, 2015	Sec. 14 (Transp): add "propane" after Liquefied Petroleum Gas
• 4 th revision	August 31, 2015	Changed emergency contact number

Glossary

- ACGIH** – American Conference of Governmental Industrial Hygiene
- DOT** – US Department of Transportation
- DSL** – Domestic Substance List (Canada)
- E2** – Environmental Emergencies (Canada)
- GHS** – Globally Harmonized System
- IARC** – International Agency for Research on Cancer
- IDLH** – Immediately Dangerous to Life and Health
- NIOSH** – National Institute for Occupational Safety & Health
- NPRI** – National Pollutant Release Inventory (Canada)
- NTP** – National Toxicology Program
- OSHA** – Occupational Safety & Health Administration of the US Dept of Labour
- PEL** – Permissible Exposure Limit
- SARA** – Superfund Amendments and Reauthorization Act of 1986
- STEL** – Short Term Exposure Limit
- TRI** – US Toxic Release Inventory
- TSCA** – Toxic Substance Control Act
- TWA** – Time Weighed Average

Disclaimer of Expressed and Implied Warranties

The information presented in the Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. However, neither Keyera nor its affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

~ End of Safety Data Sheet ~